
5/5/ 13/30 10/30 1 r103 107 117b 117d 117a/ 117c/ 102 73 104 田 74d74c 74a. 52 51b 53 75b 75c 75d 75a 78 51a' 94 F16. 29 58 61 57b 76' 55 57a 77a56 86 84 82 2006 88/ 35 81b 81c 80 26 - F 33´ 38 36) 31 83 87 39 32, COORDINATE SYSTEM 85 -37

FIG. 2



F1G. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7A




FIG. 7B




FIG. 8





FIG. 9



F1G.10




FIG. 11

URL http://www.maintain.co.jp/db/input.html
PROBLEM DB INPUT SCREEN
INPUT
TYPE ******** 1401
NAME OF PROBLEM OPERATION FAILURE (START-UP ERROR) 1403
DEVICE 465NS4580001 -1402
DEGREE OF D 1405
DATE OF OCCURRENCE 27 DEC 2000 1404
SIGN OF PROBLEM
LED LIT INTERMITTENTLY AFTER POWER IS SUPPLIED 1406
COUNTERMEASURE
SUPPLY POWER AGAIN (PRESS RED BUTTON AT START) 1407
PROGRESS
PROBLEM COUNTERED TENTATIVELY 1408
(SEND) (RESET)
LINK TO LIST OF 1410 1411 1412 DATA BASE OF RESULT SOFTWARE LIBRARY OPERATION GUIDE

FIG. 12




FIG. 13




FIG. 14




FIG. 15A





FIG. 15B



ì

F1G. 16A




FIG. 17A





FIG. 17B



F1G. 18A




FIG. 19





FIG. 20



- --- UPPER LEFT CORNER
- --- LEFT CENTER PORTION
- --- RIGHT CENTER PORTION
- ---- LOWER RIGHT CORNER
- FLOWING-OUT PORT